

PRO® 1113N Harness Wrap Tape



Technical Data Sheet

Pro® 1113N is a polyester cotton blend pressure sensitive adhesive tape.

Features & Benefits:

Excellent conformability

Good typing, bundling and holding tape

Abrasion resistance makes for a good protective tape

Technical Data

- ⇒ Backing: Polyester Cotton Blend
- ⇒ Adhesive: Rubber based
- ⇒ Tensile strength: 42 lbs. per inch
- ⇒ Elongation: 5%
- ⇒ Total Thickness: 10.5 mils
- ⇒ Adhesion to steel: 32 oz./in
- ⇒ Service Temperature: 50°F to 200°F
- ⇒ Color Available: Natural/White

Application:

Pro® 1113N is used a harness wrap tape. Pro® 1113N can also be used for bundling of molding, coils, metals and sealing of cans in the baking industry.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.