

PRO® 130 Heavy Duty Duct



Technical Data Sheet

Pro® 130 is a premium, heavy duty grade cloth duct tape natural rubber adhesive base with waterproof polyester/cotton blend cloth backing.

Features & Benefits:

Waterproof Backing
Highly Conformable
Easy Unwind
Aggressive Adhesive
Indoor/Outdoor use
Excellent high tack

Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Polyethylene film with a polyester/cotton blend cloth carrier
- ⇒ Thickness: 12.5 mils
- ⇒ Tensile strength: 34 lbs. per inch
- ⇒ Elongation: 14%
- ⇒ Adhesion to steel: 56 oz./in
- ⇒ Colors: Silver, Black, Olive Drab, White
- ⇒ Service Temperature Range: 50°F to 200°F
- ⇒ Standards: Meets UL 723, FSI 10/SDI 10

Application:

Pro® 130 is typically used in motorsports, silk screening, plastering, stucco masking, HVAC dust systems, bundling, seaming, sealing and splicing.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.