

PRO® 139 Fluorescent Duct Tape



Technical Data Sheet

Pro® 139 is a specialty grade duct tape available in four brilliant fluorescent col-

Features & Benefits:

Waterproof Backing
High Visible
Highly Conformable
Easy Unwind
Aggressive Adhesive
Indoor/Outdoor use
Excellent high tack & adhesion
Competitively priced

Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Backing: Poly coated cloth
- ⇒ Thickness: 9.0 mils
- ⇒ Tensile strength: 22 lbs. per inch
- ⇒ Elongation: 16%
- ⇒ Adhesion to steel: 50 oz./in
- ⇒ Colors: FL Pink, FL Orange, FL Green, FL Yellow
- ⇒ Service Temperature Range: 50°F to 200°F

Application:

Pro® 139 is used for sealing cartons, binding books, bundling, repairing seats, color coding, splicing and general repairing. Pro® 139 Fluorescent Duct Tape is commonly used in the following industries: hospitality, motion picture, motor sports, audio visual and floral.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.