

PRO® 15 Non-skid Grit Tape



Technical Data Sheet

Pro® 15 is a commercial grade non-skid silicon carbide grit tape that has been designed to meet OSHA standards for general purpose anti-slip surface applications.

Features & Benefits:

Acrylic adhesive bond strengthens with time and heat
Designed to meet OSHA Standards
NFSI certified for “High Traction”

Technical Data

- ⇒ Surface compatibility: Painted wood, painted metal, sealed concrete, fiberglass
- ⇒ Adhesive: Permanent Acrylic
- ⇒ Color: Black
- ⇒ Tack (PASTC-6): Rolling Ball Tack
- ⇒ Adhesive Thickness: 20.0 mils
- ⇒ Backing Thickness: 2.0 mils
- ⇒ Liner Thickness: 6.0 mils
- ⇒ Grit Level: 80
- ⇒ Peel Adhesion (24 hr. dwell, PSTC-101): 130 oz. per inch
- ⇒ Peel Adhesion (Immediate, PSTC-101): 80 oz. per inch
- ⇒ Shear Adhesion (PSTC-107): Stainless Steel- 5 hours
- ⇒ Coefficient of Friction (ASTM D1894): Dry Rubber (1.2), Wet Rubber (1.1), Dry Leather (1.0), Wet Leather (1.4)
- ⇒ Solvent Resistance Recommendations: Water, 10% Salt Water, Bleach, 25% Sulfuric Acid, Diesel Fuel, Hydraulic Fluid, 50% Anti-freeze in Water, Mineral Spirits, 99% IPA
- ⇒ Solvent Resistance Not Recommended: Trichloroethylene, 1% Sodium Hydroxide, Unleaded Gasoline MEK
- ⇒ Application Temperature: 50°F or above
- ⇒ Service Temperature: -20°F to 150°F
- ⇒ Storage Recommendations: 72°F, 52% Relative Humidity
- ⇒ Latex Free
- ⇒ Must be applied to a smooth surface
- ⇒ Permanent use only

Application:

Pro® 15 is an abrasive grain coated plastic film, one-sided pressure sensitive adhesive, protected by a removable liner. Pro® 15 is a grit based anti-slip tape with an aggressive adhesive system that conforms to irregular surfaces. Pro® 15 is designed for indoor and outdoor applications that require long term anchorage to a wide variety of surfaces. It has been successfully used in a wide variety of markets including OEM, Action Sports, and Building Safety. Pro® 15 is NFSI certified for “High Traction”.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.