

PRO® 155

ADHESIVE TRANSFER TAPE



Technical Data Sheet

Pro® 155 is an adhesive transfer tape.

Features & Benefits:

Easy to remove from liner

High tack, “permanent” adhesion

390°F heat resistance

Acrylic adhesive will not bleed into most paper stocks, minimizes discoloration of print materials

Technical Data

- ⇒ Liner thickness: 2.5 mils
- ⇒ Adhesive: Acrylic
- ⇒ Tape thickness without liner: 2.0 mils
- ⇒ Color: Transparent
- ⇒ Adhesion to steel: 20 oz./in
- ⇒ Low temperature application: 10°F
- ⇒ Heat resistance: 390°F
- ⇒ 3” I.D. Core

Application:

Pro® 155 is an excellent adhesive for flying splices on paper, films, and foil. This product can be used for laminating, mounting and nameplate applications. Pro® 155 is ideal for use with high processing temperatures and for use in dry tunnel printers. Performance proven dependability promotes production line efficiencies in paper and film industries.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.