



A Shurtape Technologies, LLC Company

# PRO® 156 ATG

## 5 MIL REVERSE WOUND ADHESIVE TRANSFER TAPE

### Technical Data Sheet

**Pro® 156 ATG is a 5 mil reverse wound adhesive transfer tape on a kraft liner.**

#### **Features & Benefits:**

- Extremely high adhesion
- Good shear strength
- Excellent gap filling properties
- Exhibits good adhesion to polyester and polyether foams

#### **Technical Data**

- ⇒ Liner: 60# 4 mil Moisture Stable Kraft Liner
- ⇒ Adhesive: 5 mil Acrylic
- ⇒ Thickness without liner: 5.0 mils
- ⇒ Tape Thickness: 9.0 mils
- ⇒ Color: Transparent
- ⇒ Adhesion to steel: 75 oz./in
- ⇒ Low temperature application: 10°F
- ⇒ Heat resistance: 250°F
- ⇒ Application Temperature Range: 70°F to 100°F
- ⇒ Reverse wound ATG format on 1" I.D. Plastic Cores to fit all standard ATG dispensers
- ⇒ Pro ATG HD Dispenser with extended nose works for all sizes.
- ⇒ MIL-P-19834B, Amend I
- ⇒ Chemical Resistance: Medium
- ⇒ Not intended for direct UV Light.

#### **Application:**

Pro® 156 ATG can be used as a laminating adhesive for foam, fabrics, metal or plastic nameplates and is an excellent product for splicing of films, fabrics and foils. It is also suited for joining materials with irregular or textured surfaces.



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*