



TAPES

A Shurtape Technologies, LLC Company

PRO® 156

5 MIL 3" I.D. Core ADHESIVE
TRANSFER TAPE

Technical Data Sheet

Pro® 156 is a 5 mil adhesive transfer tape

Features & Benefits:

Extremely high adhesion
Good shear strength
Excellent gap filling properties

Technical Data

- ⇒ Liner: 60# 4 mil Moisture Stable Kraft Liner
- ⇒ Adhesive: 5 mil Acrylic
- ⇒ Thickness without liner: 5.0 mils
- ⇒ Tape Thickness with liner: 9.0 mils
- ⇒ Color: Clear
- ⇒ Adhesion to steel: 75 oz./in
- ⇒ Low temperature application: 10°F
- ⇒ Heat resistance: 250°F
- ⇒ Application Temperature Range: 70°F to 100°F
- ⇒ 3" ID Core
- ⇒ MIL-P-19834B, Amend I
- ⇒ Chemical Resistance: Medium
- ⇒ Not intended for direct UV Light.

Application:

Pro® 156 can be used as a laminating adhesive for foam, fabrics, metal or plastic nameplates and is an excellent product for splicing of films, fabrics and foils. It is also suited for joining materials with irregular or textured surfaces.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.