

# PRO<sup>®</sup> 160 Transparent Duct Tape



## Technical Data Sheet

**Pro<sup>®</sup> 160 is a latex-free versatile, waterproof, poly/scrim transparent duct tape.**

### **Features & Benefits:**

Superior water resistance

High performance acrylic adhesive system

Easy cross tear

See through backing will not obscure print or instructions on the covered surface

### **Technical Data**

- ⇒ Backing: Biaxially oriented polypropylene
- ⇒ Adhesive: Acrylic Resin
- ⇒ Thickness: 6.0 mils
- ⇒ Tensile strength: 36 lbs. per inch
- ⇒ Elongation: 20%
- ⇒ Adhesion to steel: 36 oz./in
- ⇒ Application Temperature: up to 200°F
- ⇒ Color: Transparent

Based on information obtained from its suppliers, Pro Tapes & Specialties (PTS) certifies that the following parts are fully RoHS-3 compliant to the European Union (E.U.) RoHS Directive and that no ATS products contain Substances of Very High Concern (SVHC) as listed by the European Chemicals Agency (ECHA) under the provisions of (EC) No. 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH). The product(s) referenced below DO NOT CONTAIN any of the 205 REACH Substances of Very High Concern (SVHC) as updated by ECHA on January 15, 2020 beyond their applicable %w/w tolerances.

### **Application:**

Pro<sup>®</sup> 160 can be used in a wide range of sealing, joining and protecting applications. Also used for repairing, binding and hinging.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*