

PRO® 167 Filament Tape



Technical Data Sheet

Pro® 167 is a general purpose polypropylene packaging tape reinforced with continuous glass-yarn filaments.

Features & Benefits:

Printable on adhesive side only

Saves time because of ease of dispensing

Long term holding power

High tensile strength allows use of less tape in many applications and lowers cost per application.

Technical Data

- ⇒ Backing: Polypropylene
- ⇒ Adhesive: Rubber resin
- ⇒ Thickness: 6.0 mils
- ⇒ Tensile strength: 300 lbs. per inch
- ⇒ Adhesion to steel: 50 oz./in
- ⇒ Elongation: 4%

Application:

Pro® 167 is a general purpose polypropylene packaging tape reinforced with continuous glass-yarn filaments that give the tape high tensile strength and low stretch. The clear backing provides excellent abrasion and moisture resistance. The aggressive packaging-grade adhesive is specifically formulated to provide an excellent balance of high initial adhesion and long term holding power to most fiberboard surfaces. When used in bundling, reinforcing, or coil tabbing applications, where high temperatures and/or oily surfaces are involved, tests should be conducted per the individual application before extensive use to determine the tape's suitability.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.