

PRO® 17

Vinyl Anti-skid



Technical Data Sheet

Pro® 17 is an embossed anti-slip PVC that has been engineered with an aggressive adhesive system to adhere to a wide variety of surfaces.

Features & Benefits:

Quality raw materials for long life and durability

Fine textured film improves traction in both wet and dry areas.

Easy installation, simply position, peels off backing paper, and applies to a clean, dry, oil free surface

Low profile reduces trip hazards

Technical Data

- ⇒ Surface compatibility: Painted wood, painted metal, sealed concrete, fiberglass
- ⇒ Adhesive: Permanent Acrylic
- ⇒ Color: White, Clear, Sandstone
- ⇒ Tack (PASTC-6): Rolling Ball Tack (< 5 in)
- ⇒ Adhesive Thickness: 18.0 mils
- ⇒ Backing Thickness: 2.0 mils
- ⇒ Liner Thickness: 7.0 mils
- ⇒ Peel Adhesion (24 hr. dwell, PSTC-101): Stainless Steel (75oz/in), Powder coated surfaces (55oz/in), Polyethylene (25oz/in)
- ⇒ Shear Adhesion (PSTC-107): Stainless Steel (< 5 hours)
- ⇒ Coefficient of Friction (ASTM D1894): Dry Rubber (1.05), Wet Rubber (1.06), Dry Leather (0.27), Wet Leather (0.90)
- ⇒ Solvent Resistance Recommendations: Water, 10% Salt Water, Bleach, 1% Sodium Hydroxide, Diesel Fuel, Hydraulic Fluid, 50% Anti-freeze in Water, Mineral Spirits, 99% IPA, Unleaded Gasoline
- ⇒ Solvent Resistance Not Recommended: Trichloroethylene, 25% Sulfuric Acid, MEK
- ⇒ Application Temperature: 50°F or above
- ⇒ Service Temperature: -20°F to 150°F
- ⇒ Storage Recommendations: 72°F, 50% Relative Humidity
- ⇒ Latex Free
- ⇒ Must be applied to a smooth surface
- ⇒ Permanent use only

Application:

Pro® 17 is a premium vinyl anti-skid tape used in a wide variety of applications from stairs, to boats, to bookshelves. Pro® 17 is a calendared film, characterized by moderate tensile strength, high elongation and good tear strength. Calendaring has built-in stresses that are a common cause of film shrinkage and affect dimensional stability. Pro® 17 is designed for indoor non-skid applications that require long term anchorage to a wide variety of flat surfaces. It has been successfully used in applications such as showers and tubs.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.