

PRO® 180 110LB Filament Tape



Technical Data Sheet

Pro® 180 is a utility grade fiberglass reinforced strapping tape.

Features & Benefits:

Outstanding holding power
Excellent adhesion to kraft cartons
Aggressive rubber based adhesive system

Technical Data

- ⇒ Backing: 1.0 mil Biaxially Oriented Polypropylene Film
- ⇒ Reinforcement: Fiberglass
- ⇒ Adhesive: Synthetic rubber resin
- ⇒ Tensile strength: 110 lbs. per inch
- ⇒ Elongation: 3.5%
- ⇒ Total Thickness: 4.0 mils
- ⇒ Adhesion to steel: 63 oz./in
- ⇒ Color: Clear

Application:

Pro® 180 is a utility grade fiberglass reinforced tape designed for a majority of packaging, palletizing and unitizing applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.