

PRO® 187 Flatback Paper Tape



Technical Data Sheet

Pro® 187 is a general purpose flatback paper tape.

Features & Benefits:

Excellent holding power
Resists curling
Abrasion resistant
Water resistant
Conformable backing

Technical Data

- ⇒ Backing: Extensible, kraft, flatback paper
- ⇒ Adhesive: High tack, thermoplastic rubber
- ⇒ Tensile strength (machine direction): 35 lbs. per inch
- ⇒ Tensile strength (cross direction): 22 lbs. per inch
- ⇒ Elongation: 6%
- ⇒ Total Thickness: 6.0 mils
- ⇒ Adhesion to steel: 110 oz./in
- ⇒ Service Temperature: 60°F to 150°F
- ⇒ Specification: ASTM D 6123/D 6123M-07 (2012), Type II; FDA Indirect Contact CFR 21 - 174.5, 175.105, 176.170 & 176.180

Application:

Pro® 187 is a general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching tape that will stick to a wide variety of substrates. Pro® 187 is also used for hand and machine carton sealing and splicing of various substrates. Also used in floor seaming applications.



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.