



Tapes & Specialties

621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

PRO® 20 Heavy Duty SPVC Pipe Wrap

Technical Data Sheet

Pro® 20 is a heavy duty SPVC pipe wrap tape.

Features & Benefits:

UL Listed

Vapor and moisture barrier

Highly conformable

Good abrasion, impact and rupture resistance

Resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals

Technical Data

- ⇒ Backing: Soft PVC (Polyvinyl Chloride)
- ⇒ Adhesive: Rubber Based
- ⇒ Total Tape Thickness: 20.0 mils
- ⇒ Tensile Strength: 32 lbs. per inch
- ⇒ Elongation: 300%
- ⇒ Adhesion to steel: 11 oz. per inch
- ⇒ Colors: Black
- ⇒ Temperature Resistance: 14°F to 176°F
- ⇒ Flame Resistance: UL510

Application:

Pro® 20 is typically used as pipe wrap and surface protection tape. Pro® 20 provides electrical protection, as well as protection for pipe joints, conduit couplings for overhead or direct buried applications. Pro® 20 is an excellent masking tape for hard chrome plating and anodizing.

ISO 9001
Certified



WARNING: This product can expose you to chemicals including Diisononyl phthalate (DINP), which is known to the State of California to cause cancer and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.