

# PRO<sup>®</sup> 200 Textured Vinyl Tape



## Technical Data Sheet

**Pro<sup>®</sup> 200 is a white textured vinyl tape on a liner.**

### Features & Benefits:

Seaming tape for vinyl faced fiberglass insulation, ie: metal buildings  
Resists to water, detergent, alcohol, aliphatic and some aromatic hydrocarbons

Flexible

Conformable

### Technical Data

- ⇒ Liner: 42# SCK White coated with silicone on one side
- ⇒ Adhesive: Acrylic
- ⇒ Peel Adhesion: 3.0 lbs. per inch
- ⇒ Sheer Strength: 10hrs.
- ⇒ Total Thickness: 3.2 mils
- ⇒ Loop Tack: 1.8lbs per inch
- ⇒ Release Range: 15 to 50g per inch
- ⇒ Adhesive coat weight: 1.75 g/100 in<sup>2</sup>, +/- 10%
- ⇒ Application Conditions: 40°F to 120°F. Apply to clean, dry surfaces for best results.
- ⇒ Storage Conditions: Store at 60°F to 80°F, 50% RH

### Application:

Pro<sup>®</sup> 200 is a white textured vinyl tape that is flexible and conformable. Pro<sup>®</sup> 200 offers durability and moisture resistance. This product utilizes a high performance tackified acrylic adhesive. Pro<sup>®</sup> 200 is used as a seaming tape for fiberglass insulation. *Pro<sup>®</sup> 200 is not recommended for use when in contact with active solvents such as ketones, esters and some chlorinated hydrocarbons.*

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*