



PRO® 200HD

Embossed White Vinyl Seaming Tape

Technical Data Sheet

Pro® 200HD is a Matte Vinyl Seaming Tape with a Kraft Liner and a Acrylic Adhesive System.

Features & Benefits:

- Matte finish vinyl
- Good quick stick properties
- Good temperature and humidity performance to work in any weather
- Plasticizer resistant adhesive

Technical Data:

- ⇒ Liner:40# White Kraft
- ⇒ Adhesive: Acrylic
- ⇒ Carrier: Matte White Vinyl Taffeta
- ⇒ Liner Thickness : 2.5 mils
- ⇒ Adhesive Thickness: 1.5 mils
- ⇒ Carrier Thickness: 3.4 mils
- ⇒ Total Thickness (with liner): 7.4 mils
- ⇒ Total Thickness (without liner): 4.9
- ⇒ Tensile Elongation: 135%
- ⇒ Minimum Application Temperature: 0°F
- ⇒ Maximum Continuous Operating Temperature: 200°F
- ⇒ Maximum Intermittent Operating Temperature: 225°F
- ⇒ Color: White

Application:

Pro® 200HD is commonly used as a seaming tape for vinyl faced fiberglass insulation (i.e. metal buildings).

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105