



TAPES

A Shurtape Technologies, LLC Company

PRO® 3032

Double Coated Foam Tape

Technical Data Sheet

Pro® 3032 is a double-coated foam tape developed for general purpose bonding applications.

Features & Benefits:

Supplied self-wound on a densified, semi-bleached kraft release liner. Adhesion bonds to most surfaces including low energy materials such as polyethylene and polypropylene. 1/32" foam carrier provides a gap filling function that aids in the joining of uneven or irregular surfaces.

Technical Data

- ⇒ Liner: 83# White SCK
- ⇒ Adhesive: Rubber
- ⇒ Thickness: 1/32"
- ⇒ Elongation: 355%
- ⇒ Adhesion to steel: 137 oz. per inch
- ⇒ Tensile Strength: 213 lbs. per inch
- ⇒ Max Temperature: 180°F
- ⇒ Recommended Application Temperature: 50°F

Application:

Pro® 3032 is a double-coated foam tape developed for general purpose bonding applications. Pro® 3032 is an 1/32" thick white, closed cell polyethylene foam coated on both sides with an aggressive, general purpose, rubber based pressure sensitive adhesive.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.