

PRO® 400 Double Sided Paper



Technical Data Sheet

**Pro® 400 is a 3.5mil impregnated crepe paper coated on both sides
with a 2.5mil rubber adhesive.**

Features & Benefits:

High Tack
Moderate shear properties
Good tensile strength

Technical Data

- ⇒ Tape construction: Double coated paper tape
- ⇒ Adhesive (liner and exposed side): Rubber
- ⇒ Liner: 60# White densified kraft
- ⇒ Carrier: 3.5mil Yellow crepe paper
- ⇒ Peel exposed side: 80 oz/in, high
- ⇒ Peel liner side: 80 oz/in, high
- ⇒ Liner side loop tack: High
- ⇒ Liner side RT shear: Moderate
- ⇒ Exposed side loop tack: High
- ⇒ Exposed side RT shear: Moderate
- ⇒ Shear exposed side: 7+ days
- ⇒ Shear liner side: 7+ days
- ⇒ Total Thickness: 8.5 mils
- ⇒ Service Temperature: 30°F to 150°F

Application:

Pro® 400 is used where an economical, general purpose double coated paper tape with good tensile strength is needed. It is also used for bonding and laminating to a wide variety of plastics, metals, papers, also various types of parts to be machined. Also used in splicing and core start up applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.