

PRO® 408

Double Coated Polyester Tape



Technical Data Sheet

Pro® 408 is a double coated polyester film tape coated on both sides with an aggressive acrylic pressure sensitive adhesive.

Features & Benefits:

Excellent adhesion to a wide variety of surfaces

Excellent resistance to:

Oils, some plasticizers, ultraviolet light, and can withstand higher temperatures than a rubber based adhesive

pH Neutral

Technical Data

- ⇒ Carrier: PET, 0.5mil polyester
- ⇒ Adhesive: Solvent Acrylic
- ⇒ Liner Thickness: 4 mils
- ⇒ D/C Adhesive Thickness: 3 mils
- ⇒ Total Thickness: 7.5 mils
- ⇒ Elongation: 3.50%
- ⇒ Initial Tack: 20cm (3 in., 11mm steel ball)
- ⇒ 180°F Peel adhesion: 45 oz./in (71 oz. /24mm, 20min dwell on stainless steel)
- ⇒ Application Temperature: 50°F to 104°F
- ⇒ Service Temperature: -4°F to 212°F

Application:

Pro® 408 is used for bonding and laminating to a wide variety of cloths, vinyl's, corks, paper, rigid and flexible plastics. Pro® 408 is commonly used for mounting displays, such as signs, covers, posters and name plates.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.