

PRO® 5050C



EHB (Extreme High Bond) Tape

Technical Data Sheet

Pro® 5050C EHB (Extreme High Bond) Tape is used in many indoor and outdoor applications.

Features & Benefits:

Modified acrylic adhesive bonds well to metals, glass, painted surfaces and medium/low surface energy plastics
Acrylic foam combines a high level of internal strength
20mil Thickness helps adhesion to irregular surfaces

Technical Data

- ⇒ Adhesive: Modified Acrylic
- ⇒ Thickness: 20.0 mils
- ⇒ Tensile strength: 75 lbs. per inch
- ⇒ Density: 56 lbs. per feet
- ⇒ 90°F Peel adhesion: 17 lbs. per inch
- ⇒ Release Liner: 5mil Red Polyethylene
- ⇒ Color: Clear
- ⇒ UV Resistance: Excellent
- ⇒ Solvent Resistance: Excellent
- ⇒ Temperature Resistance: 248°F

Application:

Pro® 5050C is used in many indoor and outdoor applications. EHB Tape often replaces spot welds, rivets, nails, liquid adhesives and other permanent fasteners.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.