



# PRO® 5100C

# EHB (Extreme High Bond) Tape

# TAPES

A Shurtape Technologies, LLC Company

## Technical Data Sheet

**Pro® 5100C EHB (Extreme High Bond) Tape is used in many indoor and outdoor applications.**

### Features & Benefits:

Modified acrylic adhesive bonds well to metals, glass, painted surfaces and medium/low surface energy plastics  
 Acrylic foam combines a high level of internal strength  
 40mil Thickness helps adhesion to irregular surfaces

### Technical Data

- ⇒ Adhesive: Modified Acrylic
- ⇒ Thickness: 40.0 mils
- ⇒ Tensile strength: 86 lbs. per inch
- ⇒ Density: 56 lbs. per feet
- ⇒ 90°F Peel adhesion: 19 lbs. per inch
- ⇒ Release Liner: 5mil Red Polyethylene
- ⇒ Foam Color: Clear
- ⇒ UV Resistance: Excellent
- ⇒ Solvent Resistance: Excellent

### Application:

Pro® 5100C is used in many indoor and outdoor applications. EHB Tape often replaces spot welds, rivets, nails, liquid adhesives and other permanent fasteners.

ISO 9001  
 Certified



621 Route One South. North Brunswick, NJ 08902  
 Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*