

# PRO® 5110G

# EHB (Extreme High Bond) Tape



## Technical Data Sheet

**Pro® 5110G EHB (Extreme High Bond) Tape is used in many indoor and outdoor applications.**

### **Features & Benefits:**

Modified acrylic adhesive bonds well to metals, glass, painted surfaces and medium/low surface energy plastics  
Acrylic foam combines a high level of internal strength  
45mil Thickness helps adhesion to irregular surfaces

### **Technical Data**

- ⇒ Adhesive: Modified Acrylic
- ⇒ Thickness: 45.0 mils
- ⇒ Tensile strength: 86 lbs. per inch
- ⇒ Density: 52 lbs. per feet
- ⇒ 90°F Peel adhesion: 22 lbs. per inch
- ⇒ Release Liner: 5mil Red Polyethylene
- ⇒ Foam Color: Gray
- ⇒ UV Resistance: Excellent
- ⇒ Solvent Resistance: Excellent
- ⇒ Temperature Resistance: Long Term: 212°F, Short Term: 320°F

### **Application:**

Pro® 5110G is used in many indoor and outdoor applications. EHB Tape often replaces spot welds, rivets, nails, liquid adhesives and other permanent fasteners.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*