



PRO® 514

Double-coated Poly Sheeting Tape

Technical Data Sheet

Description:

Pro® 514 is a double-coated tape used for sheeting and draping.

Features & Benefits:

- Hand tearable and durable
- Once applied, conformable and moisture resistant
- High strength to hang sheeting material for asbestos abatement and expansive drapes.
- Easy to use and easy to remove

Technical Data

- ⇒ Adhesive: Rubber/Acrylic
- ⇒ Liner: Kraft Paper
- ⇒ Colors: Blue
- ⇒ Thickness without liner: 9.83 mils
- ⇒ Thickness with liner: 13.33 mils
- ⇒ Tensile strength: 30 lbs. per inch
- ⇒ Adhesion to steel (open side): 21.4 oz. per inch
- ⇒ Adhesion to steel (liner side): 89 oz. per inch
- ⇒ Elongation: 7%

Application:

Pro® 514 is used for securing tarps or poly sheeting materials to surfaces such as wood, glass, aluminum, plastics, vinyl and painted surfaces. Pro® 514 is designed to hold materials in place without damaging painted or finished surfaces for 14 days.



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105