



Tapes & Specialties

621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

PRO® 603 Pipe Wrap

Technical Data Sheet

Pro® 603 is a 10 mil PVC pipe wrap tape.

Features & Benefits:

Thick

Tough

Resilient

Abrasion resistant

Highly resistant to sun, water, oil, acids and corrosive chemicals

Technical Data

- ⇒ Adhesive: Rubber based adhesive
- ⇒ Backing: Plasticized PVC
- ⇒ Thickness: 10.0 mils
- ⇒ Tensile strength: 23 lbs. per inch
- ⇒ Volume Resistance: $\times 10^{12}$ Q.cm
- ⇒ Dielectric Strength: 10,000 volts
- ⇒ Elongation: 200%
- ⇒ Adhesion to steel: 22 oz. per inch
- ⇒ Service Temperature: 14°F to 176°F
- ⇒ Colors: Black, White

Application:

Pro® 603 is a pipe wrap or surface protection tape highly resistant to sun, water, oil, acids and corrosive chemicals while providing electrical protection. Protects joints and conduit coupling for overhead or direct buried applications.

ISO 9001
Certified



WARNING: This product can expose you to chemicals including Diisononyl phthalate (DINP), which is known to the State of California to cause cancer and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.