

# PRO® 708 8-Day Painter's Tape



## Technical Data Sheet

**Pro® 708 is a 8-day safe release  
green painter's masking tape.**

### **Features & Benefits:**

- UV Resistant
- Flexible
- Conformable
- High shear values for securing drop cloths
- Consistent surface contact for secure holding power
- Resistant to paint bleed through

### **Technical Data**

- ⇒ Backing: Crepe Paper
- ⇒ Adhesive: Synthetic Rubber
- ⇒ Overall grade: Premium
- ⇒ Thickness: 5.9 mils
- ⇒ Color: Green
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Elongation: 11%
- ⇒ Adhesion to steel: 22 oz. per inch
- ⇒ Service Temperature: 50°F to 150°F
- ⇒ Not recommended for use I lacquer applications or on anodized aluminum.

### **Application:**

Pro® 708 removes cleanly from painted metal, wood, glass and sheetrock for up to 8 days. Pro® 708 is a highly conformable and UV resistant. Pro® 708 can be used as holding plastic or paper drop cloths. Pro® Scenic 708 is a high quality rubber-based adhesive system.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*