

# PRO® 721

## High Temperature Masking



### Technical Data Sheet

**Pro® 721 is a high temperature masking tape that is coated with a natural rubber adhesive.**

#### **Features & Benefits:**

- Can withstand repeated exposure cycles of 300°F for up to 1-1/2 hours
- Odor free
- Resistant to most stains & solvents
- Good elongation– conformability to irregular surfaces and around corners
- Prevents edge bleed
- Long shelf life
- Removes clean
- Excellent stick & hold

#### **Technical Data**

- ⇒ Backing: Impregnated crepe paper
- ⇒ Adhesive: Rubber/resin
- ⇒ Color: Tan
- ⇒ Total Tape Thickness: 7.3 mils
- ⇒ Tensile strength: 26 lbs. per inch
- ⇒ Elongation: 10%
- ⇒ Adhesion to steel: 28 oz/in
- ⇒ Unwind @ 150 FPM: 10 oz/in
- ⇒ Maximum Performance Temperature: 300°F
- ⇒ Specifications– CID AA-883B Type I, BAC 5317

#### **Application:**

Pro® 721 is specifically designed for high temperature paint masking applications in the housing, aerospace, truck, bus, marine and automotive markets. Pro® 721 is also designed for use as a general purpose masking as well as holding and splicing applications. Pro® 721 performs well in wet strip applications. Pro® 721 is recommended for hot to warm removal but can be removed cold.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*