

PRO® 723

High Temperature Masking



Technical Data Sheet

Pro® 723 is a high temperature masking tape that is coated with a natural rubber adhesive.

Features & Benefits:

- Can withstand repeated exposure cycles of 300F for up to 1-1/2 hours
- Odor free
- Resistant to stains & solvents
- Good elongation- conformability to irregular surfaces
- Prevents edge bleed
- Long shelf life
- Removes clean

Technical Data

- ⇒ Backing: Impregnated crepe paper
- ⇒ Adhesive: Rubber/resin
- ⇒ Color: Tan
- ⇒ Total Tape Thickness: 6.4 mils
- ⇒ Tensile strength: 22 lbs. per inch
- ⇒ Elongation: 10%
- ⇒ Adhesion to steel: 60 oz./in
- ⇒ Maximum Performance Temperature: 300°F
- ⇒ Specifications- ASTM D6123, CID-A-A-883B Type I, PPP-T-42C Type I, BAC 5034 Type IV Class 3E, BAC 5317, BAC 5336, BAC 5578, BAC 5598, BAC 5657

Application:

Pro® 723 is specifically designed for high temperature paint masking applications in the housing, aerospace and automotive markets.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.