

PRO® 730

Glass Cloth Tape



Technical Data Sheet

Pro® 730 is a glass cloth substrate with a proprietary rubber based adhesive.

Features & Benefits:

Economical

Glass cloth backing provides abrasion protection and puncture resistance

Conforms well to uneven surfaces

Rubber adhesive system is designed to resist flagging and contamination

Technical Data

- ⇒ Backing: 5.0 mil Glass Cloth
- ⇒ Adhesive: Rubber Thermosetting
- ⇒ Color: White
- ⇒ Total Tape Thickness: 7.0 mils
- ⇒ Tensile strength: 170 lbs. per inch
- ⇒ Elongation: 8%
- ⇒ Adhesion to steel: 40 oz./in
- ⇒ Dielectric Breakdown: 2
- ⇒ Specifications: UL List E82910. MIL-I-15126 Type GFT

Application:

Pro® 730 is used for coil wraps, cross-over insulation and coil banding. Pro® 730 is an economical and cost effective tape for RF shielding and electroplating applications. Pro® 730 is used for maximum resistance to flagging and varnish solvents and is non-corrosive. Glass Cloth backing provides abrasion protection and puncture resistance. Pro® 730 conforms to uneven surfaces. Pro® 730 has a rubber adhesive system that is designed to resist flagging and contamination from varnish chemicals or solvents.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.