

PRO® 785

Contractor Grade Masking Tape



Technical Data Sheet

Pro® 785 is a rubber based adhesive crepe paper

professional grade masking tape.

Features & Benefits:

- Flexible
- Conforms well to irregular surfaces
- Good quick stick
- Easy release off of the roll
- Paint and sundries industry standard

Technical Data

- ⇒ Backing: Impregnated crepe paper
- ⇒ Adhesive: Synthetic rubber/resin
- ⇒ Color: Natural
- ⇒ Total Tape Thickness: 5.8 mils
- ⇒ Tensile strength: 23 lbs. per inch
- ⇒ Elongation: 9%
- ⇒ Adhesion to steel: 39 oz./in
- ⇒ Service Temperature: 50°F to 200°F
- ⇒ Government Specifications: ASTM D6123/D6123M-07 Type I, PPP-T-42C Type I

Application:

Pro® 785 provides excellent adhesion to a wide variety of surfaces in a number of fields including commercial and residential painting and construction, industrial masking, holding and packaging.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.