

PRO® 795

General Purpose Masking Tape



Technical Data Sheet

Pro® 795 is a rubber based adhesive crepe paper

general purpose masking tape.

Features & Benefits:

- Clean removal from most surfaces
- Conforms well to irregular surfaces
- Adheres well to a variety of substrates
- Economically priced

Technical Data

- ⇒ Backing: Impregnated crepe paper
- ⇒ Adhesive: Synthetic rubber
- ⇒ Color: Natural
- ⇒ Total tape thickness: 4.6 mils
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Elongation: 7%
- ⇒ Adhesion to stainless steel: 30 oz./in
- ⇒ Service temperature range: 60°F - 150°F
- ⇒ Specifications: ASTM D 6123/D 6123M-97 (2012), Type I

Application:

Pro® 795 provides excellent adhesion to a wide variety of surfaces in a number of fields including light bundling, light duty masking, and packaging or sealing.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.