

PRO® 804L Aluminum Foil Tape



Technical Data Sheet

Pro® 804L is a 3 mil aluminum foil tape with liner.

Features & Benefits:

- High tensile aluminum alloy
- Coated with an aggressive adhesive system
- Can be applied at low temperatures
- Can be used on irregular and curved surfaces because of the nature of dead soft aluminum
- Excellent for die-cutting

Technical Data

- ⇒ Backing: 3.0 Mil Dead Soft Aluminum
- ⇒ Adhesive: Solvent Based Acrylic
- ⇒ Liner: Removable Paper
- ⇒ Total Thickness: 4.8 mils
- ⇒ Peel Adhesion: 72 oz./in.
- ⇒ Elongation: 5.5%
- ⇒ Service Temperature: -30°F to 302°F

Application:

Pro® 804L is a high performance 3.0mil dead soft aluminum foil with liner. Pro® 804L dead soft aluminum foil tape offers a high performance adhesive system with temperature capabilities for use in vapor barrier protections, water proof dealing heat reflection/dissipation and reliable properties for masking in paint stripping and electroplating.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.