

PRO® 808L Aluminum Foil Tape



Technical Data Sheet

Pro® 808L is an aluminum foil tape.

Features & Benefits:

- High tensile aluminum alloy
- Coated with an aggressive adhesive system
- Can be applied at low temperatures
- Can be used on irregular and curved surfaces because of the nature of dead soft aluminum

Technical Data

- ⇒ Backing: Dead Soft Aluminum
- ⇒ Adhesive: Acrylic
- ⇒ Thickness: 3.6 mils (PSTC-33, ASTM D3652)
- ⇒ Adhesion to steel: 73 oz./in. (PSTC-33, ASTM D3330)
- ⇒ Tensile Strength: 17.1 lbs./in. (PSTC-33, ASTM D3759)
- ⇒ Elongation: 3.5% (PSTC-33, ASTM D3759)
- ⇒ Service Temperature: -22°F to 248°F

Application:

Pro® 808L is a high performance 2.0mil dead soft aluminum foil with liner. Pro® 808L dead soft aluminum foil tape offers a high performance adhesive system with temperature capabilities for use in vapor barrier protections, water proof dealing heat reflection/dissipation and reliable properties for masking in paint stripping and electroplating.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.