



PRO® 819 FSK

FSK (FOIL SCRIM KRAFT) TAPE

Technical Data Sheet

Pro® 819 FSK is an aggressive all-weather acrylic adhesive system.

Features & Benefits:

- An aggressive all-weather acrylic adhesive system
- Bonds tightly and permanently to insulation facing and HVAC ducts
- Performs well over a wide range of environmental conditions

Technical Data:

- ⇒ Film: FSK (Foil Scrim Kraft)
- ⇒ Adhesive: Solvent Acrylic
- ⇒ Liner: 60-lb Silicone Coated Kraft
- ⇒ Total Thickness without Liner: 6.5 mils
- ⇒ Peel Adhesion to Stainless Steel: 70 oz./inch
- ⇒ Tensile Strength: 40 lbs./inch
- ⇒ Elongation: 2%
- ⇒ Service Temperature: -25°F - 240°F
- ⇒ Color: Clear

Application:

Pro® 819 FSK is used sealing cold and dual temperature duct seams and joints where FSK is the basic insulation facing.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105