

PRO® 910

Optically Clear Polypropylene Tape



Technical Data Sheet

Pro® 910 is an optically clear Polypropylene Tape coated with a non-yellowing adhesive system.

Features & Benefits:

- High strength polypropylene backing offers excellent edge tear and split resistance
- Maintains performance and appearance when exposed to UV light
- Solvent resistant
- Abrasion resistant
- Optically clear

Technical Data

- ⇒ Backing: Polypropylene Film
- ⇒ Adhesive: Solvent Based Acrylic
- ⇒ Total Tape Thickness: 2.0 mils (+/- .5 mil)
- ⇒ Tensile strength: 20 lbs. per inch
- ⇒ Elongation: 140%
- ⇒ Adhesion to steel: 25 oz. per inch, +/- 7 oz. per inch
- ⇒ Application Temperature Range: 20°F to 110°F
- ⇒ Service Temperature Range: -20°F to 180°F
- ⇒ Government Specification: CID A-A-1684C

Application:

Pro® 910 is specifically designed for laminating and repairs where clarity and strength are extremely important. Pro® 910 is also an industrial strength, brilliantly clear film tape developed for use in packaging, carton sealing, overlays and laminating and label protection, along with edge reinforcement.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.