



TAPES

A Shurtape Technologies, LLC Company

PRO® 917

House Wrap Tape

Technical Data Sheet

Pro® 917 House Wrap Tape is a polyester film, single coated with an aggressive acrylic adhesive.

Features & Benefits:

- Exhibits excellent aging and weathering properties.
- Maintains adhesion at low temperatures.
- Excellent balance of tack, peel and tensile strength.
- Printable PET carrier adds dimensional stability and strength.
- Aggressive, tacky adhesive aides in splicing to various no silicone surfaces.

Technical Data:

- ⇒ Adhesive: Acrylic
- ⇒ Adhesive Thickness: 1.5 mils
- ⇒ Backing: Polyester Film
- ⇒ Backing Thickness: 1.5 mils
- ⇒ Total Thickness; 3.0 mils
- ⇒ Elongation: 110%
- ⇒ Peel Adhesion: 40 oz./inch
- ⇒ Tensile Strength: 37 lbs./inch
- ⇒ Color: Red, White, Clear
- ⇒ Maximum Continuous Use Temperature: 230°F
- ⇒ Minimum Application Temperature: 0°F

Application:

Pro® 917 is a polyester film, single coated with an aggressive acrylic adhesive. Pro® 917 common applications include house wrapping, sealing seams, joints, crawl spaces, foam insulation boards, and vapor barriers.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.