

PRO® 925

Polyester Carton Sealing Tape



Technical Data Sheet

**Pro® 925 is a high performance polyester packaging
and label protection tape.**

Features & Benefits:

- Polyester backing
- Pressure sensitive hot melt rubber-resin adhesive
- Adheres instantly to most surfaces including cartons containing high levels of recycled content
- Abrasion resistant backing with high edge tear and split resistance
- High performance ensures reliable closures

Technical Data

- ⇒ Backing: 1.0 mil Biaxially Oriented Polyester Film
- ⇒ Adhesive: Hot rubber-resin
- ⇒ Color: Clear
- ⇒ Total Tape Thickness: 1.9 mil
- ⇒ Tensile strength: 25 lbs. per inch (MD) 30 lbs. per inch (CD)
- ⇒ Elongation: 110%
- ⇒ Adhesion to steel: 45 oz./in
- ⇒ Storage Temperature: 40°F to 80°F, 50% Relative Humidity

Application:

Pro® 925 is used for box sealing, splicing, re-cooperage and other demanding packaging applications. This product has a strong abrasion resistant backing and the most consistent pressure sensitive hot melt adhesive system available. This time proven construction assures high performance in a wide range of environments and applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.