



PRO® 931

Single Coated Polyethylene Tape

Technical Data Sheet

Pro® 931 is a heavy-duty, polyethylene film, single coated with a synthetic rubber pressure sensitive adhesive.

Features & Benefits:

- Provides a water tight seal and humidity resistance in a range of weather conditions
- Low residue aggressive adhesive allowing material to be repositioned
- Bonds well to most surfaces over a wide temperature range
- Serrated edge option facilitates easy tear by hand
- Higher tack with excellent bond strength
- Increased thickness for additional durability
- Good conformability for application to rough or irregular surfaces
- This professional grade product is also formulated to meet the FR requirements of both NFPA 701 and ASTM E84 standards.

Technical Data:

- ⇒ Backing: Polyethylene film
- ⇒ Adhesive: Synthetic rubber
- ⇒ Total Thickness: 9.0 mils
- ⇒ Adhesive Thickness: 3.5 mils
- ⇒ Tensile Strength: 22 lbs./inch
- ⇒ Peel Adhesion: 85 oz./inch
- ⇒ Elongation: 100%
- ⇒ Operating Temperature Range: 32°F-160°F
- ⇒ Color: White
- ⇒ Passes the flame retardant requirements of the National Fire Protection Association (NFPA) 701 standard.
- ⇒ Conforms to the ASTM buildings materials fire test E84 – Class 1 or A rating.

Application:

Pro® 931 common applications include agricultural general purpose repair and protection, Wire identification, High durability surface protection, Polyethylene splicing. General industrial masking, bundling, splicing and repair applications. All-purpose waterproof sealing applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105