

# PRO® 960

## Polyester Film Tape



### Technical Data Sheet

**Pro® 960 is a polyester film, single coated with a  
silicone pressure sensitive adhesive.**

#### **Features & Benefits:**

- High temperature silicone adhesive
- Withstands 425°F baking cycles
- Removes cleanly after use
- Good conformability
- Good chemical & solvent resistance

#### **Technical Data**

- ⇒ Backing: 2.0 mil Polyester
- ⇒ Adhesive: 1.4 mil Silicone
- ⇒ Color: Green
- ⇒ Total Tape Thickness: 3.4 mils
- ⇒ Adhesion to steel: 35 oz./in
- ⇒ Dielectric Strength: 9000 volts
- ⇒ Maximum Temperature: 425°F (Short term)

#### **Application:**

Pro® 960 is used for masking in powder coated applications. Designed to withstand baking cycles of 425°F with clean, residue free removal.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*