

# PRO® 99 Fiber Film Tape



## Technical Data Sheet

**Pro® 99 is a semi-transparent tape featuring a high tack, aggressive adhesive and hand tearable film/fiber backing.**

### Features & Benefits:

- High tack, aggressive adhesive
- Abrasion resistance
- Easily used without the aid of a dispenser
- Printed data on containers and cartons won't be obliterated
- Sticks to treated paper overwraps
- Resists flagging and contamination from varnish chemicals or solvents
- High tensile strength
- Abrasion resistant

### Technical Data

- ⇒ Backing: Polyester Film / Non-woven
- ⇒ Adhesive: Rubber Thermosetting
- ⇒ Color: Semi-transparent
- ⇒ Total Tape Thickness: 5.0 mils
- ⇒ Backing Thickness: 4.0 mils
- ⇒ Tensile strength: 60 lbs. per inch
- ⇒ Elongation: 100%
- ⇒ Adhesion to steel: 35 oz. per inch
- ⇒ UL Listed (E82910)
- ⇒ Insulation class: 130°C
- ⇒ Dielectric Strength: 5,000 volts

### Application:

Pro® 99 can be used for general purpose sealing and attaching, especially used on treated paper overwraps and other “hard-to-stick-to” surfaces. Pro® 99 was designed for use in holding and insulation applications during transformer and coil manufacturing.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*