

# PRO® Dual-Tack Floor Secure Tape

Double Coated Temporary Floor/Wall Tape



A Shurtape Technologies, LLC Company

## Technical Data Sheet

**Pro® Dual-Tack Floor Secure Tape is a double coated floor hold down application tape.**

### Features & Benefits:

Easy to use and remove cleanly  
Excellent for temporary holding  
Strong adhesion

### Technical Data

- ⇒ Adhesive: Synthetic rubber-based/aggressive natural rubber
- ⇒ Liner: Blue LDPE
- ⇒ Liner thickness: 2.25 mils
- ⇒ Total thickness without liner: 16.08 mils
- ⇒ Total thickness with liner: 18.33 mils
- ⇒ Tensile strength (open side): 22.5 lbs./inch
- ⇒ Tensile strength (liner side): 20 lbs./inch
- ⇒ Adhesion to steel (open side): 32.5 oz./inch
- ⇒ Adhesion to steel (liner side): 40 oz./inch
- ⇒ Elongation (open side): 10%
- ⇒ Colors: Blue (open side), White adhesive upon removing liner side

### Application:

Pro® Dual-Tack Floor Secure Tape is perfect for stages or film sets when creating specific flooring in scenes or providing a suitable surface for performers and equipment. Other applications included events like tradeshow, exhibitions, showrooms and weddings.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*