

# PRO® FAST Hook & Loop Tape



## Technical Data Sheet

**Pro® Fast is a high performance hot melt pressure sensitive adhesive hook and loop tape.**

### Features & Benefits:

- Quick stick
- Good temperature resistance
- Good low temperature performance

### Technical Data

- ⇒ Backing: 100% Nylon Fastener
- ⇒ Adhesive: Hi Tac Rubber Adhesive
- ⇒ Hook Height: 0.0146" (0.37mm)
- ⇒ Base Thickness: 0.009" (0.22mm)
- ⇒ Overall Thickness: 0.02" +/- 0.002 (0.5mm +/- 0.05)
- ⇒ Melting Point: 419°F (215°C)
- ⇒ Per Square Inch: 896 Hooks (+/- 5%)
- ⇒ Peel Strength (ASTM D5170): 0.43 lb./inch
- ⇒ Shear Strength (ASTM D5169): 20.04 lb./inch<sup>2</sup>
- ⇒ Engaged Thickness: 0.061" (1.56mm)
- ⇒ Colors Available: Black, White

### Application:

Pro® Fast is a high performance adhesive hook and loop tape having an excellent quick stick, peel adhesion to a wide variety of substrates. With Velcro-like technology, Pro® Fast closure system can be applied to rigid surfaces or it can also be sewn into fabrics.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902  
Toll Free #1-800-345-0234  
sales@protapes.com

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*