

PRO® FILLET TAPE

Double Coated Tape



Technical Data Sheet

Pro® Fillet Tape is a double coated with an acrylic solvent based adhesive.

Features & Benefits:

Highly resistant against solvent, chemical, UV and heat
Quick bond

Technical Data

- ⇒ Carrier: PET, 0.5mil polyester
- ⇒ Color: Transparent with white liner
- ⇒ Adhesive: Acrylic
- ⇒ Total thickness: 7.5 mil
- ⇒ Elongation: 3.50%
- ⇒ Initial Tack: 20cm (3 in., 11mm steel ball)
- ⇒ 180°F Peel adhesion: 45 oz/in (71 oz. /24mm, 20min dwell on stainless steel)
- ⇒ Application Temperature: 50°F to 104°F
- ⇒ pH Neutral (Level 7)

Application:

Pro® Fillet Tape is designed to attach the fillet or slip to the picture mount in the framing industry.

Pro® Fillet Tape is used for mounting decorative trims such as PVC profile for the furniture industry. Pro® Fillet Tape can also be used for fastening of nameplates, trophy, luggage tag, wooden trims and signs. Pro Fillet Tape is used for permanent bonding to most substrates, such as metal, wood, glass, cement and plastics.



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.