



PRO® Flash 65

Self-adhesive Window & Door Flashing Tape

Technical Data Sheet

Pro® Flash 65 is a self-adhering membrane PP film with butyl hybrid adhesive on a PET liner.

Features & Benefits:

- High strength micro creped PP film and adhesive which seals around nails and prevents water intrusion
- Installation temperature range 10°F to 150°F
- Butyl hybrid adhesive with excellent low and high temperature flexibility and adhesion
- Puncture resistant

Technical Data:

- ⇒ Adhesive: Butyl Hybrid
- ⇒ Backing Micro Creped PP Film
- ⇒ Liner: PET liner
- ⇒ Thickness without liner: 65 mils (ASTM D1777)
- ⇒ Peel Adhesion: (ASTM D3330 Method F)
 - OSB: 2.0 lb./in
 - Plywood: 2.5 lb./in
 - Fiberglass gypsum: 3.0 lb./in
- ⇒ WVTR: < 0.1 perms (ASTM E96 (Desiccant))
- ⇒ Sealant Compatibility: Pass (AAMA711-08 level 3)
- ⇒ Application Temperature: 10°F to 150°F
- ⇒ Service Temperature: -30°F to 200°F
- ⇒ Colors Available: White & Black

Application:

Pro® Flash 65 common applications include sealing around windows, doors, and other openings and transitions in exterior walls, which stretches in the length direction to conform around sill pans and curved penetrations

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. Adhesives are compliant with FDA regulations for indirect food contact—CFR 175.105