

PRO[®] GLOW GRIT Non-skid Grit Tape



Technical Data Sheet

Pro[®] Glow Grit is a safety grade photoluminescent non-skid grit tape coated with an aggressive pressure sensitive adhesive.

Features & Benefits:

- Safety grade
- Exceeds OSHA requirements
- Aggressive pressure sensitive adhesive
- Designed for indoor safety applications
- Meets rigid ASTM and NYC (MEA#235-05-M) standards
- Complies with all safety grade photoluminescent domestic and international standards
- Glowing duration: 10 hours

Technical Data

- ⇒ Adhesive: Natural Rubber
- ⇒ Substrate Thickness: 19.0 mils
- ⇒ Adhesive Thickness: 2.0 mils
- ⇒ Release Liner: 7.0 mils
- ⇒ Tack: < 3 inches
- ⇒ Shear Adhesion to stainless steel: 10 Hours
- ⇒ Luminance Compliance: DIN 67510, ASTM 2072, ISO 15370, MEA#235-05-M
- ⇒ Candelas: 56 mcd/m² after 10 min, 7 mcd/m² after 60 min
- ⇒ Typical Peel Adhesion Values: 90 oz./in (15 min), 110 oz/in (24 hours)

Application:

Pro[®] Glow Grit is designed to exceed requirements for OSHA and other safety standards. Pro[®] Glow Grit is designed for indoor safety applications such as egress markings in building, marine, rail, and military applications. When fully charged, Pro[®] Glow Grit provides positive luminance for up to 10 hours.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.