

PRO® GLOW STRIPES

Lane Marking Tape



Technical Data Sheet

Pro® Glow Stripes is a black/yellow striped flexible laminated, printed film that is perfect for marking pathway obstructions that may be hazardous in blackout and very smoky conditions.

Features & Benefits:

Safety grade

Excellent UV Stability

Exceeds all OSHA requirements

Designed for indoor and outdoor safety applications

Approved for low location lighting on passenger ships

Standards: DIN 67510, ASTM 2072, ISO 15370, EU marine Equipment Directive, IMO Resolution A. 752 (18), PSPA Class C, JIS Z9100, NYC RS6-1, UL 1994 Listed

Technical Data

- ⇒ Adhesive: Rubber adhesive
- ⇒ Backing: Polyester film
- ⇒ Thickness: 15.0 mils
- ⇒ Color: Black/Yellow Stripes
- ⇒ Service Temperature: -20°F-220°F
- ⇒ Sheer adhesion to stainless steel: 10 hours
- ⇒ Peel adhesion to stainless steel: 120 oz./inch (24 hour dwell)

Application:

Pro® Glow Stripes Tape is used for lane and floor marking. Pro® Glow Stripes is used for striping, warning, and marking of hazardous areas and exits to comply with OSHA requirements. This product absorbs and stores energy from ambient light and is immediately visible in sudden darkness. Pro® Glow Stripes affixes to most wood, metal, concrete, plaster, and painted surfaces. Pro Glow Stripes is perfect for low-level emergency egress system.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.