

PRO HD SAFETY STRIPES

Lane Marking Tape



Technical Data Sheet

Pro HD Safety Stripes is a heavy duty, premium grade plasticized PVC coated with a rubber adhesive.

Features & Benefits:

Heavy Duty
Highly Conformable
Satisfies and exceeds all OSHA requirements
High-wearing feature
Will not corrode, brass, steel, aluminum
Resistant to most chemicals and moisture

Technical Data

- ⇒ Adhesive: Synthetic Rubber
- ⇒ Total Thickness: 7 mils
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Elongation: 150%
- ⇒ Adhesion to steel: 22 oz./in
- ⇒ Temperature Resistance: up to 72°F
- ⇒ Storage Temperature Recommended: 72°F, 65% Relative Humidity
- ⇒ Complies with OSHA requirements per paragraph 1910.144 of the Federal Register.

Application:

Pro HD Safety Stripes has an excellent resistance to acids, alkaline, bacteria, corrosion and oils. Pro HD Safety Stripes is used for lane and floor marking. Pro HD Safety Stripes is used for striping, warning of hazardous areas and exits to comply with OSHA requirements.



WARNING: This product can expose you to chemicals including Diisononyl phthalate (DINP), which is known to the State of California to cause cancer and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.