

PRO[®] LITE 36

Reflective Films



Technical Data Sheet

Pro[®] Lite 36 is a economical reflective vinyl featuring enclosed lens and retro-reflective films.

Features & Benefits:

Economical

Designed for short-term advertising/promotion

Used for decorative striping applications

Technical Data

- ⇒ Adhesive: Acrylic
- ⇒ Outdoor Durability: 2 Years, when properly processed and applied (vertical exposure, unprinted film)
- ⇒ Minimum Surface/Ambient Air: +38°F
- ⇒ Application Temperature: +48°F, when used for short term transportation (fleet) markings
- ⇒ Application Surface: Flat
(Not recommended for unpainted stainless steel applications)
- ⇒ Service Temperature Range: -40°F to 180°F
- ⇒ Typical Film Caliper (with adhesion): 5.5 to 6.6 mils
- ⇒ Typical Adhesion: 180 Peel
- ⇒ Optical Properties; Reflective intensity– meets or exceeds L-S300C, Table IV Reflectivity 3
- ⇒ Values: Substrate
Anodized Aluminum: 3.4 (15min), 5.3 (24hrs)

Application:

Pro[®] Lite 36 is a economical reflective vinyl featuring enclosed lens and retro-reflective films which meet or exceed the applicable requirements of Federal Specifications L-2300 (reflectivity 3). Pro[®] Lite 36 films have been designed for short-term advertising/promotion, bumper stickers, vehicle emblems and a variety of decorative striping applications.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com