

# PRO® PHOTO Black Photo Tape



## Technical Data Sheet

**Pro® Photo Tape is a opaque, matte surface...**

**“the photographer’s masking tape!”**

### Features & Benefits:

Hand tearable

High conformability

Easy, consistent unwind

High quick stick adhesion

An opaque black, matte finish surface insures the light free masking required for high quality photo reproduction

### Technical Data

- ⇒ Backing: Impregnated paper
- ⇒ Adhesive: Synthetic rubber
- ⇒ Total tape thickness: 6.1 mils
- ⇒ Tensile strength: 21 lbs. per inch
- ⇒ Unwind @ 150 FPM: 25 oz. per inch
- ⇒ Adhesion to steel: 50 oz. per inch
- ⇒ Elongation: 7%
- ⇒ Service Temperature: 45°F to 100°F

### Application:

Pro® Photo Tape is engineered for quality photographic reproduction work– cropping and edging negatives; positioning negatives for contact printing; sealing camera bellows and film holders against light leaks.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

[sales@protapes.com](mailto:sales@protapes.com)

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.*