

PRO® PREMIUM BLACK MASK TAPE



Technical Data Sheet

Pro® Premium Black Mask tape is a medium crepe paper masking tape coated with pressure sensitive rubber based adhesive.

Features & Benefits:

Strong adhesion

Resistant to water, solvents and oil

Can be used in masking off areas in acrylic watercolor painting

pH Neutral

Technical Data

- ⇒ Backing: Medium crepe paper
- ⇒ Adhesive: Synthetic rubber/resin
- ⇒ Total tape thickness: 5.7 mils
- ⇒ Tensile strength: 19 lbs. per inch
- ⇒ Adhesion to steel: 32 oz. per inch
- ⇒ Quick stick to steel: 14 oz. per inch
- ⇒ Color: Black
- ⇒ Application temperature range: 50°F to 90°F
- ⇒ Operating temperature range: 40°F to 150°F
- ⇒ Not printable

Application:

Pro® Premium Black Mask is designed for light-weight packaging, bag locking, decorative edging and marking. Pro® Premium Black Mask can be used in masking off areas in acrylic and watercolor painting.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.