PRO® SPIKE STACK Stack of 4 Fluorescent Gaff Rolls

Technical Data Sheet

Pro® Spike Stack consists of four different fluorescent colored Pro Spike tapes shrink wrapped in one bundle.

Features & Benefits:

High strength, high performance adhesive system Highly conformable to irregular surfaces Weather resistant Smooth, controlled unwind High thread count Hand Tearable Abrasion resistant Clean removability from most surfaces FL Colors are UV light friendly for high visibility Used for bundling wires Used for spiking stages

<u>Technical Data</u>

- \Rightarrow Backing: Cotton Cloth
- $\Rightarrow~$ Adhesive: Synthetic rubber based
- $\Rightarrow~$ Tensile strength: 50 lbs. per inch
- \Rightarrow Elongation: 4%
- \Rightarrow Total Thickness: 11 mils
- \Rightarrow Adhesion to steel: 75 oz./in
- \Rightarrow Service Temperature: 50°F to 180°F
- ⇒ Each Stack Includes 1 Roll of Each Color: Fl. Pink, Fl. Yellow, Fl. Green, Fl. Orange

Application:

Pro® Spike Stacks are constructed of premium gaffers tape that are available in widths of 1/2"

and 1", all with a roll length of 20 yards. Pro® Spike Stacks have all the same features of a high

performance adhesive system. Pro® Spike Stacks are highly conformable to irregular surfaces.

Waterproof and abrasion resistant, Pro® Spike Stacks are used to mark stages for actors, direc-

tional signals for dark stages and color coding.

ISO 9001 Certified PERRY JOHNSON RECENTERARS INC. 621 Route One South. North Brunswick, NJ 08902 Toll Free #1-800-345-0234

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminates.



