

PRO Thread Seal Tape

P.T.F.E. Thread Seal Tape



Technical Data Sheet

Features & Benefits:

- ⇒ Multipurpose tape for all types of threaded fittings
- ⇒ Great for sealing gas, water, and other high pressure lines

Technical Data

- ⇒ **Chemical Properties:** Minimum of 99% Teflon
- ⇒ **Thickness:** 0.0035”
- ⇒ **Elongation:** Minimum of 50% (most of the time far exceeds this)
- ⇒ **Width:** Nominal width +/- 0.02”
- ⇒ **Length:** Nominal length +20”, 0”
- ⇒ **Density:** 0.4
- ⇒ **Pressure Rating:** up to 10,000-PSI
- ⇒ **Incompatibility:** Avoid using on Molten Alkali, certain Halogen products and Fluorine at high temperatures and pressures.
- ⇒ **Temperature:** -450°F to +500°F
- ⇒ **Government Standard:** Meets MIL-spec T-27730A
- ⇒ **Shelf Life:** Unlimited

Application: Pro Thread Seal Tape can be used on all types of threaded fittings for passage of water potable and non-potable, most chemicals, oxygen, gasoline, natural gas, hydraulic and high-pressure lines.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.